

# Prioritizing Highway Projects for Improvement of Evacuation



March 2014

T14-01



## **HAMPTON ROADS TRANSPORTATION PLANNING ORGANIZATION**

Dwight L. Farmer  
Executive Director/Secretary

### **VOTING MEMBERS:**

#### **CHESAPEAKE**

Alan P. Krasnoff

#### **GOULCESTER COUNTY**

John C. Meyer, Jr.

#### **HAMPTON**

George Wallace

#### **ISLE OF WIGHT COUNTY**

Delores Dee-Dee Darden

#### **JAMES CITY COUNTY**

Mary K. Jones

#### **NEWPORT NEWS**

McKinley Price

#### **NORFOLK**

Paul D. Fraim

#### **POQUOSON**

W. Eugene Hunt, Jr.

#### **PORTSMOUTH**

Kenneth I. Wright

#### **SUFFOLK**

Linda T. Johnson

#### **VIRGINIA BEACH**

William D. Sessoms, Jr.

#### **WILLIAMSBURG**

Clyde Haulman

#### **YORK COUNTY**

Thomas G. Shepperd, Jr.

### **MEMBERS OF THE VIRGINIA SENATE**

The Honorable Thomas K. Norment, Jr.

The Honorable Frank W. Wagner

### **MEMBERS OF THE VIRGINIA HOUSE OF DELEGATES**

The Honorable Christopher P. Stolle

The Honorable David Yancey

### **TRANSPORTATION DISTRICT COMMISSION OF HAMPTON ROADS**

William E. Harrell, President/Chief Executive Officer

### **WILLIAMSBURG AREA TRANSIT AUTHORITY**

Kevan Danker, Executive Director

### **VIRGINIA DEPARTMENT OF TRANSPORTATION**

James Utterback, Hampton Roads District Administrator

### **VIRGINIA DEPARTMENT OF RAIL AND PUBLIC TRANSPORTATION**

Jennifer Mitchell, Director

### **VIRGINIA PORT AUTHORITY**

Rodney Oliver, Interim Executive Director

## HAMPTON ROADS TRANSPORTATION PLANNING ORGANIZATION

### NON-VOTING MEMBERS:

**CHESAPEAKE**

James E. Baker

**GLOUCESTER COUNTY**

Brenda G. Garton

**HAMPTON**

Mary Bunting

**ISLE OF WIGHT COUNTY**

Anne Seward

**JAMES CITY COUNTY**

Doug Powell

**NEWPORT NEWS**

Jim Bourey

**NORFOLK**

Marcus Jones

**POQUOSON**

J. Randall Wheeler

**PORTSMOUTH**

John Rowe

**SUFFOLK**

Selena Cuffee-Glenn

**WILLIAMSBURG**

Jackson C. Tuttle

**YORK COUNTY**

James O. McReynolds

**FEDERAL HIGHWAY ADMINISTRATION**

Irene Rico, Division Administrator, Virginia Division

**FEDERAL AVIATION ADMINISTRATION**

Jeffrey W. Breeden, Airport Planner, Washington Airports Office District

**PENINSULA AIRPORT COMMISSION**

Ken Spirito, Executive Director

**CITIZEN TRANSPORTATION ADVISORY COMMITTEE**

Shepelle Watkins-White, Chair

**MILITARY LIAISONS**

Robert Clark, Captain, U.S. Navy

John Little, Captain, U.S. Coast Guard

John J. Allen, Jr., Colonel, Langley

William S. Galbraith, Colonel, Langley

**INVITED PARTICIPANTS**

Hollis D. Ellis, Commonwealth Transportation Board

John Malbon, Commonwealth Transportation Board

W. Sheppard Miller, III, Commonwealth Transportation Board

**FEDERAL TRANSIT ADMINISTRATION**

Brigid Hynes-Cherin, Acting Regional Administrator, Region 3

**VIRGINIA DEPARTMENT OF AVIATION**

Randall P. Burdette, Director

**NORFOLK AIRPORT AUTHORITY**

Wayne E. Shank, Executive Director

**FREIGHT TRANSPORTATION ADVISORY COMMITTEE**

Arthur Moye, Jr., Co-Chair (Nonvoting Board Member)

Delegate Christopher P. Stolle, Co-Chair (Voting Board Member)

**HRTPO and HRPDC PROJECT STAFF**

Camelia Ravanbakht, Ph.D.

Deputy Executive Director, HRTPO

Robert B. Case, Ph.D., P.E.

Principal Transportation Engineer

Kathlene Grauberger

Senior Administrative Assistant

Michael Long

General Services Manager

Christopher Vaigneur

Assistant General Services Manager

# Prioritizing Highway Projects for Improvement of Hurricane Evacuation

PREPARED BY:



MARCH 2014

## REPORT DOCUMENTATION

### TITLE

Prioritizing Highway Projects for Improvement of Hurricane Evacuation

### AUTHOR

Robert B. Case, PE, PhD

### ABSTRACT

This document records recent analysis undertaken by HRTPO staff to identify and prioritize—according to cost effectiveness—highway projects designed to improve hurricane evacuation in Hampton Roads.

### NON-DISCRIMINATION

The HRTPO assures that no person shall, on the ground of race, color, national origin, handicap, sex, age, or income status as provided by Title VI of the Civil Rights Act of 1964 and subsequent authorities, be excluded from participation in, be denied the benefits of, or be otherwise subject to discrimination under any program or activity. The HRTPO Title VI Plan provides this assurance, information about HRTPO responsibilities, and a Discrimination Complaint Form.

### REPORT DATE

March 2014

### ORGANIZATION NAME, ADDRESS, & TELEPHONE

Hampton Roads Transportation Planning Organization  
723 Woodlake Drive  
Chesapeake, Virginia 23320  
757.420.8300  
<http://www.hrtpo.org>

### ACKNOWLEDGMENTS

The idea for this study came from Bob Gey (City of Virginia Beach).

This document was prepared by the Hampton Roads Transportation Planning Organization (HRTPO) in cooperation with the U.S. Department of Transportation (USDOT), Federal Highway Administration (FHWA), Federal Transit Administration (FTA), Virginia Department of Transportation (VDOT), and Virginia Department of Rail and Public Transportation (DRPT). The contents of this report reflect the views of the HRTPO. The HRTPO staff is responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the FHWA, FTA, VDOT or DRPT. This report does not constitute a standard, specification, or regulation. FHWA, FTA, VDOT or DRPT acceptance of this report as evidence of fulfillment of the objectives of this program does not constitute endorsement/approval of the need for any recommended improvements nor does it constitute approval of their location and design or a commitment to fund any such improvements. Additional project level environmental impact assessments and/or studies of alternatives may be necessary.

---

## TABLE OF CONTENTS

Impetus; Original Analysis Plan .....	2
Literature Review for Projects and Delay .....	3
Identification of Hurricane Highway Projects .....	5
Estimation of Delay Savings.....	10
Cost Effectiveness .....	13
Conclusion and Recommendation.....	14
Appendices .....	15
Appendix A: Literature Review .....	16
Appendix B: Extracting 54 Mile DEIS Estimate .....	20
Appendix C: VDOT FY14 Six Yr. Improvement Prog.....	24
Appendix D: Public Comments .....	26

## IMPETUS

Under current conditions, in the event of a hurricane it is possible that only a portion of the people living in homes in low-lying areas of Hampton Roads will be able to evacuate. For persons with household vehicles, evacuation success is primarily a function of these variables: a) strength of the hurricane, b) the capacity of the evacuation highways, and c) the start of the evacuation process. Due to the number of households in low-lying areas, and given the current capacity of evacuation highways (including the planned reversal of I-64), it may take 36 hours to clear evacuation highways for a Category 3 storm.<sup>1</sup> However, due to the uncertainty associated with the final path of an approaching storm, local citizens and governments may not begin evacuation 36 hours before the arrival of tropical storm force winds. According to a recent report prepared for the Southeast Virginia / Northeast North Carolina Regional Catastrophic Planning Project, "...due to the geography and location of the region, it will be rare to have the lead time needed...".<sup>2</sup>

Therefore, to increase the likelihood of evacuation success, it is desirable to increase the capacity of evacuation highways. Given that no prioritized list of highway projects for improving evacuation exists for Hampton Roads, the purpose of this study is to prepare a prioritized list of highway projects that improve evacuation.

## ORIGINAL ANALYSIS PLAN

Given the staff time available for this project, the original plan for executing the subject prioritization was to obtain highway hurricane projects—and delay data with which to calculate their cost effectiveness—from existing studies via a literature review.

<sup>1</sup> *Virginia Hurricane Evacuation Study, Transportation Analysis, Commonwealth of Virginia, Coastal Jurisdictions, Summary Report* (FEMA/USACE/VDEM, May 2008), p. 3-21.

<sup>2</sup> *Phase 3 Planning Support to VMASC and the HR RCPT, Final Technical Memorandum* (FEMA/Atkins, June 2013, p. 22).

## LITERATURE REVIEW FOR PROJECTS AND DELAY

A review of recent hurricane studies was conducted to identify highway projects for improvement of evacuation and to locate delay data with which to calculate project cost effectiveness. Based on the information available in existing studies, the original analysis plan was refined.

### I. Documents Reviewed

The following recent hurricane studies were reviewed (see Appendix A for review information from each document):

#### A. SE Virginia / NE North Carolina Regional Catastrophic Planning Project

Evacuation Behavioral Study (SocResearch Miami, March 2010)

Evacuation and Transportation Plan Review Findings Report (Dewberry/PBS&J, March 2010)

Evacuation Traffic and Evacuee Participation Monitoring Report (Dewberry/PBS&J, April 2010)

Report on Transportation Requirements for Evacuation (Dewberry/PBS&J, draft Aug. 2010)

Mass Evacuation Annex (Dewberry/PBS&J, Aug. 2010)

Evacuation Scenarios Analysis and Traffic Modeling Report (Dewberry/PBS&J, draft August 2010)

Barco Diversion/NC-VA Border Traffic Control Plan Analysis (Dewberry/Atkins, Aug. 5, 2011)

Assessment of VDOT Bowers Hill Improvement Alternatives to Ease Evacuation (Atkins, draft Oct. 2011)

Phase 3 Planning Support to VMASC and the HR RCPT (Atkins, June 2013)

### B. Other Efforts

An Operational Analysis of the Hampton Roads Hurricane Evacuation Traffic Control Plan (Phase 1) (VTRC, Jan. 2006)

An Operational Analysis of the Hampton Roads Hurricane Evacuation Traffic Control Plan – Phase 2 (VTRC, Apr. 2008)

Virginia Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008)

Hampton Roads Hurricane Evacuation Transportation Study (VMASC, June 27, 2008)

Highway Evacuations in Selected Metropolitan Areas: Assessment of Impediments (FHWA, April 2010)

Hurricane Evacuation Modeling of the Hampton Roads Region (VCTIR, draft May 2012)

Behavioral Study Report; Refuge of Last Resort Study Report; Shelter Study Report; Housing Study Report (VMASC, June 2013)

## II. Refinement of Analysis Plan

The above review of recent evacuation documents—conducted to obtain hurricane highway projects and delay data with which to calculate project cost effectiveness—revealed:

- a) evacuation-improving highway projects:

The Assessment of VDOT Bowers Hill Improvement Alternatives to Ease Evacuation (Atkins, draft Oct. 2011) identified a preferred highway project for lane reversal on the Southside—reversal of VA168/I-64/US58 in Chesapeake and Suffolk<sup>3</sup>—and estimated its clearance-time reduction (19 hours).

The Highway Evacuations in Selected Metropolitan Areas (FHWA, April 2010) includes a statement of the impediment provided by traffic signal timing (see Appendix A for details) which led staff to consider the potential benefit of special event signal timing for hurricane evacuation.

- b) delay data:

The Virginia Hurricane Evacuation Study, or VHES (VDEM/USACE/FEMA, May 2008) produced an Abbreviated Transportation Model (ATM) spreadsheet which estimates the clearance time<sup>4</sup> for 31 “Critical Roadway Segments”.

Given that the review revealed only one specific hurricane highway project (VA168/I-64/US58 Southside reversal), plus pointed to one type of hurricane highway project (special evacuation signal timing), the original analysis plan outlined above for this FY14 evacuation highway project prioritization was refined as follows:

### Refined Analysis Plan

Use the 31 Critical Roadway Segments in the VHES to develop a list of highway projects designed to improve the evacuation of vehicles using those segments, considering the above projects (the Chesapeake/Suffolk reversal project and the retiming of signals along signalized evacuation routes) as possible candidates.

Ask VDOT to estimate the cost of the above projects, and use those costs, and the clearance times and number of evacuating vehicles from the VHES, to calculate the cost effectiveness of the subject projects.

<sup>3</sup> Note that an earlier Southside reversal project—different from the preferred one in the Atkins document—is partially funded in VDOT’s Six-Year Improvement Program [see Appendix C for details].

<sup>4</sup> “Clearance time is the time required to clear the roadway of all vehicles evacuating in response to a hurricane situation.” (VHES, Transportation Analysis, Summary Report, VDEM/USACE/FEMA, May 2008, p. 3-16.)

## IDENTIFICATION OF HIGHWAY PROJECTS FOR IMPROVING HURRICANE EVACUATION

Given that the literature review revealed only one specific hurricane highway project (VA168/I-64/US58 Southside reversal) plus one type of hurricane highway project (special evacuation signal timing), staff used the 31 Critical Roadway Segments in the Virginia Hurricane Evacuation Study (VHES) to develop a list of highway projects designed to improve the evacuation of vehicles using those segments, considering the Chesapeake/Suffolk reversal project and the retiming of signals along signalized evacuation routes as possible candidates.

### Criteria

Staff identified a hurricane improvement project to address the evacuation delay on VHES Critical Roadway Segments with large need for evacuation improvement, considered to be those segments with an estimated **clearance time exceeding 18 hours**. The primary exceptions were:

- segments covered by a committed highway project
- segments covered by a hurricane improvement project already identified in this study.

The table below records the process of examining each of the 31 Critical Roadway Segments. For each segment, the table contains either a hurricane improvement project or explanation of project omission.

## Table 1- Identification of Highway Projects for Improving Hurricane Evacuation (page 1 of 4)

Source: HRTPO (addressing high clearance times from ATM.xlsx)

### Key

Segments with a hurricane evacuation improvement project identified.

This database: Critical Roadway Segments from Abbreviated Transportation Model (ATM) of Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), sorted by Clearance Time

<u>Segment</u> (Critical Roadway Segments from ATM <sup>4</sup> )	<u>Clearance Time, hours</u> (from ATM <sup>4</sup> )	<u>Highway Project for Improvement of Evacuation</u> (identified by HRTPO staff)	<u>Comment</u> (by HRTPO staff)
US 58 Suffolk Bypass	35.8	168/64/58 Southside Reversal  (i.e. the highlighted option in VDOT's 12-15-11 HRTPO Board presentation [Option 2]- two crossovers: one on Rt 168 [Oak Grove Connector] and one on I-264 approaching Bowers Hill.)	n.a.

Constance Rd btwn. Wilroy Rd & Main St

34.3 See Southside Reversal project above.

It is expected that the Southside Reversal project (above) would lower the clearance time of this segment because evacuees approaching the 58/58Bus split (on the regular WB lanes) near the SPSA landfill have a choice between the Suffolk Bypass and Portsmouth Blvd / Constance Rd. Therefore, no evacuation improvement project is identified for this segment.

Portsmouth Blvd btwn. Suffolk Byp & Nans. Pkwy

30.8 See Southside Reversal project above.

It is expected that the Southside Reversal project (above) would lower the clearance time of this segment because evacuees approaching the 58/58Bus split (on the regular WB lanes) near the SPSA landfill have a choice between the Suffolk Bypass and Portsmouth Blvd / Constance Rd. Therefore, no evacuation improvement project is identified for this segment.

Suffolk Bypass btwn. Ports. Blvd & Godwin Blvd

30.8 See Southside Reversal project above.

This segment is covered by the "US 58 Suffolk Bypass" segment above.

**Table 1- Identification of Highway Projects for Improving Hurricane Evacuation (page 2 of 4)**

<u>Segment</u> (Critical Roadway Segments from ATM <sup>4</sup> )	<u>Clearance Time, hours</u> (from ATM <sup>4</sup> )	<u>Highway Project for Improvement of Evacuation</u> (identified by HRTPO staff)	<u>Comment</u> (by HRTPO staff)
St Pauls Blvd btwn. Brambleton Ave & I-264	<b>27.7</b>	n.a. (see comment)	The calculation of this 27.7 hours for this segment was based on 32,010 evacuating vehicles, an inordinately high number given a) that it's 40% of the total Norfolk evacuating vehicles (81,896) and b) that only 10,732 evacuating vehicles from Norfolk are attempting to evacuate by western gateways (US13, US58, US460, VA10), and c) there are many other ways to reach I-264 in Norfolk.
Evacuation Timing Plans for US 17 Signals			
US 17 (JCMB <sup>3</sup> ) btwn. I-64 and Victory Blvd	<b>24.8</b>	(for all signals from I-64 to Gloucester Courthouse, i.e. beyond the area of significant background traffic, excluding signals in York County [which have an adaptive timing system rendering special timing plans unnecessary])	n.a.
HRBT Build-8 Alternative			
I-64 WB- HRBT	<b>23.2</b>	(add 2 lanes in each direction from I-564 to I-664 [DEIS, Dec. 2012])	n.a.
US 460 westbound out of region	<b>22.8</b>	n.a. (see comment)	The committed Commonwealth Connector (US 460) project will address this high clearance time.
I-64 btwn. I-564 and Bay Ave	<b>22.4</b>	See HRBT project above.	This segment is covered by the HRBT project above.

Table 1- Identification of Highway Projects for Improving Hurricane Evacuation (page 3 of 4)

Segment (Critical Roadway Segments from ATM <sup>4</sup> )	Clearance Time, hours (from ATM <sup>4</sup> )	Highway Project for Improvement of Evacuation (identified by HRTPO staff)	Comment (by HRTPO staff)
I-64 in Western NN	22.1	I-64 Peninsula Widening  (54 Mile portion of Alt. 2B in I-64 Peninsula DEIS, i.e. widen to 6-8 lanes from mm 254 [Bland Blvd] to mm 200 [I-295])	Note: Even with reversal, these outbound lanes (2 regular WB and 2 reversed EB) have a high clearance time (22.1 hours).
US 58 westbound out of region	20.8	US 58 Widening  (widen to 6 lanes from Suffolk Bypass [at Holland Rd] to I-95)	Note: Due to lack of significant destinations and cross highways between Suffolk and Emporia, this widening must continue west until reaching I-95 at Emporia.
I-64- High Rise Bridge	18.8	See Southside Reversal project above.	The Southside Reversal project (above) covers this segment via the Rt 168 crossover included in that project.
Park Ave btwn. PA Rd and Brambleton Ave	17.7	n.a. (see comment)	Less than 18 hour clearance.
I-264 westbound just east of BH <sup>1</sup>	16.5	n.a. (see comment)	Less than 18 hour clearance.
Fox Hill Rd btwn. Woodland Rd and Mercury Blvd	16.5	n.a. (see comment)	Less than 18 hour clearance.
Mercury Blvd btwn. Fox Hill Rd and Lasalle Ave	15.7	n.a. (see comment)	Less than 18 hour clearance.
I-64 toward BH just east of BH <sup>1</sup>	13.5	n.a. (see comment)	Less than 18 hour clearance.
Dam Neck Rd btwn. Gen Booth Blvd & Holland Rd	11.4	n.a. (see comment)	Less than 18 hour clearance.
Rt 10 westbound out of region	10.9	n.a. (see comment)	Less than 18 hour clearance.
US 17 out of region	10.8	n.a. (see comment)	Less than 18 hour clearance.
US 60 westbound out of region	9.7	n.a. (see comment)	Less than 18 hour clearance.
I-264 WB- Newtown Rd to I-64	8.7	n.a. (see comment)	Less than 18 hour clearance.
VA 168 south of I-64	8.6	n.a. (see comment)	Less than 18 hour clearance.
US 13 southbound out of region	7.1	n.a. (see comment)	Less than 18 hour clearance.
Northampton Blvd btwn. Dia. Sprs. Rd and I-64	6.2	n.a. (see comment)	Less than 18 hour clearance.

**Table 1- Identification of Highway Projects for Improving Hurricane Evacuation (page 4 of 4)**

<b>Segment</b> (Critical Roadway Segments from ATM <sup>4</sup> )	<b>Clearance Time, hours</b> (from ATM <sup>4</sup> )	<b>Highway Project for Improvement of Evacuation</b> (identified by HRTPO staff)	<b>Comment</b> (by HRTPO staff)
I-64 Peninsula out of region	n.a.	n.a. (see comment)	ATM gives no reversal-based clearance time for this segment, so see similar "Western NN" segment above.
I-64 btwn. exits 242 and 238	n.a.	n.a. (see comment)	ATM gives no reversal-based clearance time for this segment, so see similar "Western NN" segment above.
I-64 btwn. HRCP <sup>2</sup> and JCMB <sup>3</sup>	n.a.	n.a. (see comment)	ATM gives no reversal-based clearance time for this segment, so see similar "Western NN" segment above.
I-64 btwn. I-664 and Mercury Blvd	n.a.	n.a. (see comment)	ATM gives no reversal-based clearance time for this segment, so see similar "Western NN" segment above.

**Notes**

<sup>1</sup>BH: Bowers Hill

<sup>2</sup>HRCP: Hampton Roads Center Pkwy

<sup>3</sup>JCMB: J Clyde Morris Blvd

<sup>4</sup>ATM: Abbreviated Transportation Model (ATM) of Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008)

Scenario: Category 3, I-64 reversal, high seasonal occupancy, medium response (6 hr's), heavy background traffic

Concerning the second project above—Evacuation Timing Plans for US 17 Signals—note that a linked pair of signal coordination projects (currently without an evacuation timing component) are under development: "Signal Coordination Along Route 17" (UPC 98806) funded via regional Congestion Management Air Quality (CMAQ) funds in the FY14 VDOT Six-Year Improvement Program (SYIP) (see details in Appendix C), and "Route 17 Signal System Upgrades" (UPC 103763) in the VDOT Project Pool.

## ESTIMATION OF DELAY SAVINGS EXPECTED FROM HURRICANE HIGHWAY PROJECTS

In order to calculate the cost effectiveness of the five (5) evacuation-improving highway projects identified above, the delay savings of each project was estimated using the clearance times from the Virginia Hurricane Evacuation Study (VHES) as shown in the table found on the following pages.

Note that these calculations exclude the effect of vehicles shifting from an unimproved evacuation corridor to the subject improved corridor. The fact that delay savings at the improved corridor will be lower than the savings calculated below is mitigated by the fact the delay savings at the unimproved corridors is not included in the calculation below.

## Table 2- Delay Savings for Hurricane Highway Projects

### (page 1 of 2)

Source: HRTPO (addressing high clearance times from ATM.xlsx)

#### Project #1: 168/64/58 Southside Reversal

Clearance Time	35.8 hours	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Response Period	<u>6 hours</u>	Source:	Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), p. 2-12
Maximum Delay	<u>29.8 hours</u>		
Average Delay / Maximum Delay	<u>0.5</u>	Source:	estimate
Average Delay	<u>14.9 hours</u>		
Delay Reduction from Project	40%	Source:	19 hours / 48 hours = 0.40; Adkins document, p. 5 <sup>2</sup>
Evacuating Vehicles	<u>97,700 vehicles</u>	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Avg. Delay Savings	<u>582,292 veh-hrs</u>		

#### Project #2: US 17 Evacuation Timing Plans (I-64 to Gloucester Courthouse)

Clearance Time	24.8 hours	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Response Period	<u>6 hours</u>	Source:	Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), p. 2-12
Maximum Delay	<u>18.8 hours</u>		
Average Delay / Maximum Delay	<u>0.5</u>	Source:	estimate
Average Delay	<u>9.4 hours</u>		
Delay Reduction from Project	25%	Source:	estimate <sup>3</sup>
Evacuating Vehicles	<u>26,332 vehicles</u>	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Avg. Delay Savings	<u>61,880 veh-hrs</u>		

#### Project #3: HRBT Build-8 Alternative (DEIS)

Clearance Time	23.2 hours	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Response Period	<u>6 hours</u>	Source:	Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), p. 2-12
Maximum Delay	<u>17.2 hours</u>		
Average Delay / Maximum Delay	<u>0.5</u>	Source:	estimate
Average Delay	<u>8.6 hours</u>		
Delay Reduction from Project	50%	Source:	4 lanes existing vs. 8 lanes proposed, i.e. 100% increase in capacity <sup>4</sup>
Evacuating Vehicles	<u>61,993 vehicles</u>	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Avg. Delay Savings	<u>266,570 veh-hrs</u>		

## Table 2- Delay Savings for Hurricane Highway Projects

### (page 2 of 2)

Source: HRTPO (addressing high clearance times from ATM.xlsx)

#### Project #4: I-64 Peninsula Widening (Alt. 2B, DEIS, mm254 to mm200)

Clearance Time	22.1 hours	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Response Period	6 hours	Source:	Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), p. 2-12
Maximum Delay	16.1 hours		
Average Delay / Maximum Delay	0.5	Source:	estimate
	Average Delay	8.05 hours	
Delay Reduction from Project	33%	Source:	estimate <sup>5</sup>
Evacuating Vehicles	101,857 vehicles	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Avg. Delay Savings	270,583 veh-hrs		

#### Project #5: US 58 Widening (6 lanes from Holland Rd to I-95)

Clearance Time	20.8 hours	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Response Period	6 hours	Source:	Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008), p. 2-12
Maximum Delay	14.8 hours		
Average Delay / Maximum Delay	0.5	Source:	estimate
	Average Delay	7.4 hours	
Delay Reduction from Project	33%	Source:	estimate <sup>6</sup>
Evacuating Vehicles	51,613 vehicles	Source:	Abbreviated Transportation Model (ATM) <sup>1</sup>
Avg. Delay Savings	126,039 veh-hrs		

#### Notes

<sup>1</sup>Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008)

<sup>2</sup>Assessment of VDOT Bowers Hill Improvement Alternatives to Ease Evacuation (Atkins, Draft, Oct. 2011)

<sup>3</sup>60% signal G/C for "main street" existing timing vs. 80% G/C hurricane timing, i.e. 33% increase in capacity or 25% decrease in delay

<sup>4</sup>100% increase in capacity results in 50% decrease in delay

<sup>5</sup>2 lanes WB existing vs. 3 lanes WB proposed west of exit 247 (DEIS, pg. 11-9), i.e. 50% increase in capacity or 33% decrease in delay

<sup>6</sup>2 lanes WB existing vs. 3 lanes WB proposed, i.e. 50% increase in capacity or 33% decrease in delay

## COST EFFECTIVENESS

Combining the above-calculated delay savings with project costs (from VDOT<sup>5</sup>) and the number of evacuating vehicles using the project (from the VHES), staff calculated two cost effectiveness measures as shown in the table at right:

- Cost per Evacuating Vehicle
- Cost per Hour of Delay Saved

Regardless of the measure used, the first two projects—168/64/58 Southside Reversal and Evacuation Timing Plans for US 17 Signals—are much more cost effective than the other three projects.<sup>6</sup>

**Table 3- Cost Effectiveness of Hurricane Highway Projects**

Source: HRTPO (addressing high clearance times from ATM.xlsx)

Project	VDOT <sup>2,4</sup> Cost Estimate, avg. cost, \$m	Evacuating Vehicles (\$m from ATM <sup>1</sup> )	Cost per Evacuating Vehicle, \$ (quotient of numbers at left)	Delay Savings, veh-hrs (source <sup>3</sup> )	Cost per Hour of Delay Saved, \$
<u>168/64/58 Southside Reversal</u>					
(i.e. the highlighted option in VDOT's 12-15-11 HRTPO Board presentation [Option 2]- two crossovers: one on Rt 168 [Oak Grove Connector] and one on I-264 approaching Bowers Hill.)	\$10	97,700	\$102	582,292	\$17
<u>Evacuation Timing Plans for US 17 Signals<sup>4</sup></u>					
(for all signals from I-64 to Gloucester Courthouse, i.e. beyond the area of significant background traffic, excluding signals in York County [which have an adaptive timing system rendering special timing plans unnecessary])	\$0.019	26,332	\$0.72	61,880	\$0.31
<u>HRBT Build-8 Alternative<sup>5</sup></u>					
(add 2 lanes in each direction from I-564 to I-664 [DEIS, Dec. 2012])	\$4,950	61,993	\$79,848	266,570	\$18,569
<u>I-64 Peninsula Widening<sup>2</sup></u>					
(54 Mile portion of Alt. 2B in I-64 Peninsula DEIS, i.e. widen to 6-8 lanes from mm 254 [Bland Blvd] to mm 200 [I-295])	\$3,165	101,857	\$31,073	270,583	\$11,697
<u>US 58 Widening</u>					
(widen to 6 lanes from Suffolk Bypass [at Holland Rd] to I-95)	\$1,225	51,613	\$23,734	126,039	\$9,719

### Notes

<sup>1</sup>ATM: Abbreviated Transportation Model (ATM) of Va. Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008) Scenario: Category 3, I-64 reversal, high seasonal occupancy, medium response (6 hr's), heavy background traffic

<sup>2</sup>Note: The I-64 Peninsula Widening cost estimate is an extraction of the cost of the subject 54 mile project from the cost of the entire 75 mile VDOT DEIS project performed by HRTPO staff using the DEIS cost estimate details. See "Extracting 54 mile (254-200mm) DEIS Estimate from 75 mile (265-190mm) DEIS Estimate" in appendix.

<sup>3</sup>See "Delay Savings for Hurricane Highway Projects" in this report.

<sup>4</sup>Note: The cost estimate shown here for the timing plans is a modification of the cost estimate received from VDOT in that the cost of plans for signals in York County (which have an adaptive system) were excluded.

<sup>5</sup>Source: I-64 Hampton Roads Bridge-Tunnel Draft EIS and Draft Section 4(f) Evaluation (VDOT, Dec. 2012), p. S-5.

## CONCLUSION

### Findings

As seen in Table 3 above and Figure 1 at right, the cost effectiveness of the five hurricane highway projects place those projects into two categories:

- Highly Cost Effective for Evacuation
  - 168/64/58 Southside Reversal
  - Evacuation Timing Plans for US 17 Signals
- Less Cost Effective for Evacuation
  - HRBT Build-8 Alternative
  - I-64 Peninsula Widening
  - US 58 Widening


### Recommendation

Given the high cost effectiveness of the 168/64/58 Southside Reversal and Evacuation Timing Plans for US 17 Signals in Newport News and Gloucester, staff recommends that the HRTPO Board and VDOT consider funding these two projects.

### Future Steps

Given the high cost effectiveness of the Evacuation Timing Plans for US 17 Signals in Newport News and Gloucester, following the implementation of that project, staff recommends that the HRTPO Board and VDOT examine and consider similar evacuation timing plan projects for the following portions of VDOT evacuation routes:

- US 460 between Suffolk Bypass and I-295 near Petersburg
- Routes 32 and 10 between US 17 in Isle of Wight and I-295 near Hopewell
- US 17 between I-664 in Suffolk and I-64 in Newport News



**Figure 1- Cost Effectiveness of Hurricane Highway Projects**

Source: HRTPO (addressing high clearance times from ATM.xlsx)

## APPENDICES

## APPENDIX A: LITERATURE REVIEW FOR PROJECTS AND DELAY

A review of recent hurricane studies was conducted to identify highway projects for improvement of evacuation and to locate delay data with which to calculate their cost effectiveness.

### A. SE Virginia / NE North Carolina Regional Catastrophic Planning Project

#### Evacuation Behavioral Study (SocResearch Miami, March 2010)

This study presents the findings of a survey of citizens conducted for the study. It contains therefore neither delay information by highway segment nor evacuation-improving highway projects.

#### Evacuation and Transportation Plan Review Findings Report (Dewberry/PBS&J, March 2010)

70 plans were submitted to the authors for this review, and the authors conducted 34 interviews. The report contains neither delay information by highway segment nor evacuation highway projects.

#### Evacuation Traffic and Evacuee Participation Monitoring Report (Dewberry/PBS&J, April 2010)

This document provides information concerning traffic monitoring devices (e.g. CCTV) along evacuation routes. The report contains neither delay nor project information.

#### Report on Transportation Requirements for Evacuation (Dewberry/PBS&J, draft Aug. 2010)

The purpose of this report is to analyze the existing balance between the number of people who need assistance evacuating (herein labeled

“transportation-dependent”) and the amount of transportation resources available to meet that need. Therefore, it contains neither highway delay numbers nor highway improvement projects.

#### Mass Evacuation Annex (Dewberry/PBS&J, Aug. 2010)

The purpose of the Annex is “to provide the framework and guidelines for organizing and implementing a mass evacuation” in the local metropolitan statistical area (MSA). It contains therefore neither delay information by highway segment nor evacuation highway projects.

#### Evacuation Scenarios Analysis and Traffic Modeling Report (Dewberry/PBS&J, draft August 2010)

This report presents in-area public shelter demand numbers (by locality), inland public shelter demand numbers, and revised clearance times for the region, but showing times only for “I-64 out”, “US 58/Bowers HI”, and “local feeder routes”. Consequently this study does not provide delay-related numbers by all pertinent highway segments, neither does it provide evacuation-improving highway projects.

Barco Diversion/NC-VA Border Traffic Control Plan Analysis  
(Dewberry/Atkins, Aug. 5, 2011)

This document reflects the authors' analysis of the North Carolina/Virginia Border Traffic Control Plan, PKA "Barco Diversion Plan", a plan designed to prevent NC evacuation traffic from adding to evacuation congestion in Hampton Roads.

In the section "Roadway Improvements to Ease Evacuation Congestion", the only Virginia project is the Chesapeake/Suffolk reversal project (see "Assessment of VDOT..." below.)

Assessment of VDOT Bowers Hill Improvement Alternatives to Ease Evacuation (Atkins, draft Oct. 2011)

This study produces clearance times to measure the effectiveness of four reversal alternatives that use reversed lanes between various crossovers in Chesapeake (that place traffic on the reversed lanes) and a crossover on Suffolk Bypass just west of the US 460 exit (that returns traffic to regular lanes).

The study indicates that the Chesapeake/Suffolk reversal of VA168/I-64/US58 can reduce clearance time at the Suffolk Bypass by 19 hours.

Phase 3 Planning Support to VMASC and the HR RCPT (Atkins, June 2013)

This study contains a variety of information: Census data adjustments, public shelter demand adjustments, suggested refuges of last resort (ROLR), best practices for servicing stranded vehicles, and master timeline review.

In order to identify potential ROLR locations, the study identifies six key congestion "hotspots":

- 1) I-64 at Wards Corner
- 2) I-64 at Bland Blvd
- 3) Williamsburg Area
- 4) High-Rise Bridge
- 5) Bowers Hill Interchange
- 6) Suffolk Bypass

The focus being on ROLR, no delay or clearance times were provided for these hotspots, and no highway improvement projects were identified.

Note that, in its master timeline review, the study indicates that VDOT will keep the MMMBT open during evacuations (a change from its previous intention to close it):

"Modeling by Praveen Edara for VCTIR and further analysis/opposition from the HRTPO...convinced officials that the closure was not needed. Atkins also confirmed through this effort that closing I-664 with a reversal of I-64 through the peninsula was not needed for a major hurricane."

"VDOT's May 2013 reversal plan states that VDOT will leave open I-664 north."

## B. Other Efforts

### An Operational Analysis of the Hampton Roads Hurricane Evacuation Traffic Control Plan (Phase 1) (VTRC, Jan. 2006)

This effort used a microscopic simulation model (VISSIM) to “determine the performance characteristics with respect to traffic flow” of “the freeway portions of the evacuation routes” under VDOT’s 2001 hurricane traffic control plan for Hampton Roads.

Due to its limitation to interstates, and lack of delay output by highway segment, it is not useful for this FY14 UPWP project.

### An Operational Analysis of the Hampton Roads Hurricane Evacuation Traffic Control Plan – Phase 2 (VTRC, Apr. 2008)

As in Phase 1 above, this effort used VISSIM to evaluate the VDOT traffic control plan, but—unlike Phase 1—this effort examined arterial routes (in addition to interstate routes). The stated objectives were:

1. “estimate the traffic performance of evacuation routes and other major arterial streets”
2. “locate the major bottlenecks, congestion, or other operational difficulties”
3. “estimate the total network evacuation time”
4. “recommend amendments to the TCP [traffic control plan]”

The study identifies clogged evacuation highway segments (e.g. approach to Midtown Tunnel, approach to HRBT, and VB Blvd between Newtown Rd and Military Hwy), but the numerical results used to identify them seem counterintuitive. For example, a) Figure 3 (p. 16) shows that the base (i.e. uncongested) travel time of a 2 mile segment of arterial US 58 (VB Blvd from Newtown Rd to Military Hwy) is longer than that of a 6 mile segment of arterial US 58 (from

Military Hwy to Midtown Tunnel), b) Figure 3 (p. 16) shows that the base/uncongested travel time of a 16 mile segment of US 58 (from Midtown Tunnel to Suffolk Bypass & Wilroy Rd) is less than 16.7 minutes, whereas Google Maps estimates the travel time at 24 minutes, and c) Figure 4 (p. 16) shows no clogging of I-64 between HRBT and Ft. Eustis Blvd, a segment that includes the 4-lanes-to-2-lanes bottleneck near NN/Williamsburg Airport. Therefore, the bottleneck and delay information from this report will not be used in this FY14 hurricane project.

### Virginia Hurricane Evacuation Study (VDEM/USACE/FEMA, May 2008)

Although the study (abbreviated VHES) contains no list of highway projects for improving evacuation, it contains “clearance times” for key bottlenecks, i.e. the time it will take for evacuation-induced queues at these bottlenecks to clear. In addition, the study’s Abbreviated Transportation Model (ATM) spreadsheet—the source of the report’s clearance times—estimates the clearance times for 31 “Critical Roadway Segments”.

(Note that the study’s Abbreviated Transportation Model (ATM) also calculates “Worst Household Evacuation Commute Time”, but only for evacuating via I-64 on the Peninsula.)

### Hampton Roads Hurricane Evacuation Transportation Study (VMASC, June 27, 2008)

The Virginia Modeling, Analysis, and Simulation Center (VMASC) used a “macroscopic simulator” to “assess the viability of evacuating the Hampton Roads region” using the state’s plan. The report contains neither delay by highway segment nor recommended highway projects.

Highway Evacuations in Selected Metropolitan Areas: Assessment of Impediments (FHWA, April 2010)

The authors conducted surveys of “local authorities” in 26 metropolitan areas in US to determine “the most significant impediments along NHS routes that may impact...evacuations”. For Hampton Roads, Perry Cogburn (VDOT) was interviewed and stated the following impediments:

1. Traffic signal timing
2. Number of water crossings
3. Limited ITS deployment along key evacuation routes
4. Flood-prone infrastructure
5. Human resources to manage evacuation operations and tools

Being based on an interview, no delay information was provided.

Hurricane Evacuation Modeling of the Hampton Roads Region (VCTIR, draft May 2012)

This study, like the VHES above, produces clearance times used to test the efficacy of closing the MMMBT during evacuation, the I-64 Peninsula lane reversal, and the US 58 reversal. For this FY14 UPWP task, the clearance times of the VHES were considered the “official” times.

Behavioral Study Report; Refuge of Last Resort Study Report; Shelter Study Report; Housing Study Report (VMASC, June 2013)

Given that the first report reflects a survey of citizens, and the remaining reports deal with structures, these reports do not apply to

this FY14 effort of prioritizing highway projects to improve evacuation travel times.

## APPENDIX B: EXTRACTING 54 MILE (254-200 MILE MARKER) DEIS ESTIMATE FROM 75 MILE (265-190 MILE MARKER) DEIS ESTIMATE

Source: HRTPO using VDOT estimate (extracting 54 mile EIS est out of 75 mile EIS est.xlsx)

source for work below (unless otherwise stated): source1, appx. F, fourth page

source1: I-64 Peninsula Study, Alternatives Development Technical Memorandum, Oct. 2012

source2: I-64 Peninsula Study, Right of Way Technical Memorandum, Oct. 2012

### Assumptions:

Alternative: Alt 1B (adding GP lanes in the median)

Work (e.g. lanes added, interchanges modified): per DEIS

Cost Level: Average Cost Estimate (as opposed to Low, High)

Year of Expenditure: 2017 (per DEIS)

	original 75 mile estimate, \$M			54 mile (254-200mm) estimate, \$M		
--	--------------------------------	--	--	-----------------------------------	--	--

### EB Roadway

From	To	Zone	CMP			Length, mi.	(average), \$M	Cost / 54mile est. Ratio
			Length, mi.	Average, \$M	Cost, \$M			
190	193	Ric	3	\$14.5300	\$43.590	0	\$0.000	
193	197	Ric	4	\$12.2450	\$48.980	0	\$0.000	
197	200	Ric	3	\$7.5000	\$22.500	0	\$0.000	
200	202.5	Ric	2.5	\$12.2450	\$30.613	2.5	\$30.613	
202.5	205	Ric	2.5	\$7.7300	\$19.325	2.5	\$19.325	
205	224	Ric	19	\$7.3250	\$139.175	19	\$139.175	
224	241.5	HR	17.5	\$8.8450	\$154.788	17.5	\$154.788	
241.5	247	HR	5.5	\$9.5500	\$52.525	5.5	\$52.525	
247	255	HR	8	\$14.7600	\$118.080	7	\$103.320	
255	256	HR	1	\$17.1435	\$17.144	0	\$0.000	
256	265	HR	9	\$19.4500	\$175.050	0	\$0.000	
			75		\$821.769	54	\$499.745	
<u>recap</u>								
Ric District			34		\$304.183	24	\$189.113	0.62
HR District			41		\$517.586	30	\$310.633	0.60
			75		\$821.769	54	\$499.745	

### EB Bridges

Zone	Location	CPSF			Area (pro-rated via above ratio) \$M	Cost \$M
		Area	Average, per area	(average), \$M		
Zone 1 (Ric)	Mainline	349,042	\$305	\$106.458	217,002	\$66.186
Zone 1 (Ric)	Overpass	51,215	\$305	\$15.621	31,841	\$9.711
Zone 2 (HR)	Mainline	190,435	\$350	\$66.652	114,291	\$40.002
Zone 2 (HR)	Overpass	113,155	\$350	\$39.604	67,911	\$23.769
		703,847		\$228.335	431,044	\$139.668
<u>recap</u>						
Ric District						\$75.897
HR District						\$63.771
						\$139.668
EB Roadway and Bridges, subtotal					\$1,050.103	\$639.413
<u>recap</u>						
Ric District						\$265.010
HR District						\$374.403
						\$639.413

WB Roadway			original 75 mile estimate, \$m		54 mile (254-200mm) estimate, \$m			
<u>From</u>	<u>To</u>	<u>Zone</u>	<u>Length, mi.</u>	<u>Average, \$m</u>	<u>Cost (average), \$m</u>	<u>Length, mi.</u>	<u>Cost (average), \$m</u>	<u>Ratio, 54mile est. / 75mile est.</u>
190	193	Ric	3	\$14.4375	\$43.313	0	\$0.000	
193	197	Ric	4	\$12.2450	\$48.980	0	\$0.000	
197	202.5	Ric	5.5	\$7.5000	\$41.250	2.5	\$18.750	
202.5	224	Ric	21.5	\$7.3250	\$157.488	21.5	\$157.488	
224	241.5	HR	17.5	\$8.8450	\$154.788	17.5	\$154.788	
241.5	247	HR	5.5	\$9.5500	\$52.525	5.5	\$52.525	
247	255	HR	8	\$14.7600	\$118.080	7	\$103.320	
255	256	HR	1	\$17.1435	\$17.144	0	\$0.000	
256	258	HR	2	\$19.4500	\$38.900	0	\$0.000	
258	265	HR	7	\$21.3950	\$149.765	0	\$0.000	
			75		\$822.231	54	\$486.870	
<u>recap</u>								
Ric District			34		\$291.030	24	\$176.238	0.61
HR District			41		\$531.201	30	\$310.633	0.58
			75		\$822.231	54	\$486.870	
WB Bridges								
<u>Zone</u>	<u>Location</u>		<u>Area</u>	<u>CPSF Average, per area</u>	<u>Cost (average), \$m</u>	<u>Area (pro-rated via above ratio)</u>	<u>Cost (average), \$m</u>	
Zone 1 (Ric)	Mainline		301,433	\$305	\$91.937	182,537	\$55.674	
Zone 1 (Ric)	Overpass		51,215	\$305	\$15.621	31,014	\$9.459	
Zone 2 (HR)	Mainline		162,784	\$350	\$56.974	95,192	\$33.317	
Zone 2 (HR)	Overpass		113,155	\$350	\$39.604	66,170	\$23.160	
			628,587		\$204.136	374,913	\$121.610	
<u>recap</u>								
Ric District					\$107.558		\$65.133	
HR District					\$96.579		\$56.477	
					\$204.136		\$121.610	
WB Roadway and Bridges, subtotal					\$1,026.367		\$608.480	
<u>recap</u>								
Ric District					\$398.588		\$241.371	
HR District					\$627.780		\$367.109	
					\$1,026.367		\$608.480	

original 75 mile estimate, \$m			54 mile (254-200mm) estimate, \$m									
<b>Interchanges</b>												
Note: The DEIS estimate places large cost even on those interchanges with "None" under "Improvement Description" on Table 3 (pg. 18). (According to page 25, "tie in @ ramps = improvement cost".)												
Zone	Location	Quantity	CPEach Average	Cost (average)	Quantity (based on location)							
Zone 1 (Ric)	Urban, New	3	\$58.585	\$175.755	0							
Zone 1 (Ric)	Urban, Improve	3	\$38.080	\$114.240	1							
Zone 1 (Ric)	Rural, New	0	\$49.795	\$0.000	0							
Zone 1 (Ric)	Rural, Improve	4	\$38.080	\$152.320	4							
Zone 2 (HR)	Urban, New	5	\$67.370	\$336.850	2							
Zone 2 (HR)	Urban, Improve	6	\$52.725	\$316.350	2							
Zone 2 (HR)	Rural, New	2	\$58.585	\$117.170	2							
Zone 2 (HR)	Rural, Improve	2	\$52.725	\$105.450	2							
		25		\$1,318.135	13							
<u>recap</u>												
Ric District		10		\$442.315	5							
HR District		15		\$875.820	8							
		25		\$1,318.135	13							
Construction (rdway, bridges, interchanges), subtotal			\$3,394.606		\$1,901.102							
<u>recap</u>												
Ric District			\$1,267.164		\$696.780							
HR District			\$2,127.442		\$1,204.322							
			\$3,394.606		\$1,901.102							

Right of Way and Utilities	original 75 mile estimate, \$m				54 mile (254-200mm) estimate, \$m											
	source: source2, p. 10				source: source2, p. 10											
<u>Richmond District</u>																
	ROW				ROW											
	Cost, % of				Cost, % of											
	ROW	Portion of	Const.		ROW	Portion of	Const.									
	Take, Total	Cost	ROW Cost,		Take, Total	Cost	ROW Cost,									
	acres	Take	(average)	\$m	acres	Take	(average)	\$m								
Rural	26.9	17%	30%	\$64.36	24	38%	30%	\$80.24								
Res./Sub. Low Density	30.1	19%	57.5%	\$138.02	3	5%	57.5%	\$19.12								
Out. Bus. / Sub. High Density	71.7	45%	80%	\$457.42	36	57%	80%	\$316.85								
CBD	30.2	19%	112.5%	\$270.94	0	0%	112.5%	\$0.00								
	158.9	100%		\$930.735	63	100%		\$416.209								
<u>Hampton Roads District</u>																
	ROW				ROW											
	Cost, % of				Cost, % of											
	ROW	Portion of	Const.		ROW	Portion of	Const.									
	Take, Total	Cost	ROW Cost,		Take, Total	Cost	ROW Cost,									
	acres	Take	(average)	\$m	acres	Take	(average)	\$m								
Rural	53.1	12%	35%	\$86.39	48	20%	35%	\$85.94								
Res./Sub. Low Density	204	45%	62.5%	\$592.93	102	44%	62.5%	\$327.72								
Out. Bus. / Sub. High Density	169	37%	100%	\$786.00	85	36%	100%	\$434.43								
CBD	31.4	7%	137.5%	\$200.68	0	0%	137.5%	\$0.00								
	457.7	100%		\$1,665.989	234	100%		\$848.085								
ROW & Utilities, subtotal				\$2,596.724												
Total (Average Estimate)				\$5,991.330												

## APPENDIX C: VDOT FY14 SIX-YEAR IMPROVEMENT PROGRAM



### Six-Year Improvement Program

[Home](#)   [User's Guide](#)   [About](#)

[All Projects](#)   [Major Projects](#)   [MPO](#)   [Fund](#)   [Reports](#)

## Line Item Details

### Project Summary

UPC	95050		
Project	RTE. 58 - LANE REVERSAL		
Scope of Work	Safety		
Description	FROM: RTE 58 & RTE 13 Interchange TO: I-264 & I-64 Interchange		
Report Note	MPO project		
Fund Source	BOND/STP		

### Project Location

District	Hampton Roads	Jurisdiction	Hampton Roads District-wide	Estimates & Schedule		
				Estimated Cost (Thousands)	Schedule	
Road System	Primary	Length	15.5000 MI	Prelim. Eng. (PE)	\$950	Complete
Route	0058	Street	RTE. 58	Right of Way (RW)	\$0	N/A
MPO Area	Hampton Roads			Construction (CN)	\$0	N/A
				Total Estimate	\$950	

### Required Allocations

Fund Sources	Previous Allocations	Values in Thousands of Dollars							Required After FY2019
		FY2014	FY2015	FY2016	FY2017	FY2018	FY2019	FY2019	
Bond Proceeds: CPR Bonds	\$600	\$0	\$0	\$0	\$0	\$0	\$0		
RSTP (STP Regional): Federal	\$800	\$0	\$0	\$0	\$0	\$0	\$0		
RSTP (STP Regional): State Match	\$200	\$0	\$0	\$0	\$0	\$0	\$0		
<b>Total Funding</b>	<b>\$1,600</b>	<b>\$0</b>	<b>\$0</b>	<b>\$0</b>	<b>\$0</b>	<b>\$0</b>	<b>(\$650)</b>		

© Copyright 2008 Virginia Department of Transportation. All Rights Reserved.

VDOT Six-Year Improvement Program v1.0



## Six-Year Improvement Program

[Home](#)   [User's Guide](#)   [About](#)

[All Projects](#)   [Major Projects](#)   [MPO](#)   [Fund](#)   [Reports](#)

### Line Item Details

#### Project Summary

UPC	98806		
Project	SIGNAL COORDINATION ALONG ROUTE 17		
Scope of Work	Safety		
Description	FROM: Coleman Bridge TO: Route 17/17B Intersection		
Report Note	MPO Project.		
Fund Source	CM		

#### Project Location

District	Fredericksburg	Jurisdiction	Gloucester County	Estimated Cost (Thousands)	Schedule
Road System	Primary	Length	11.3000 MI	Prelim. Eng. (PE)	\$364 Underway
Route	0017	Street	Route 17	Right of Way (RW)	\$0 N/A
MPO Area	Hampton Roads			Construction (CN)	\$1,836 FY2015
				Total Estimate	\$2,200

#### Estimates & Schedule

#### Required Allocations

Fund Sources	Previous Allocations	Values in Thousands of Dollars						Required After FY2019
		FY2014	FY2015	FY2016	FY2017	FY2018	FY2019	
(\$)CMAQ: Federal	\$576	\$0	\$0	\$0	\$0	\$0	\$0	
(\$)CMAQ: MPO - Federal	\$528	\$0	\$771	\$0	\$0	\$0	\$0	
(\$)CMAQ: MPO - State Match	\$132	\$0	\$193	\$0	\$0	\$0	\$0	
<b>Total Funding</b>	<b>\$1,236</b>	<b>\$0</b>	<b>\$964</b>	<b>\$0</b>	<b>\$0</b>	<b>\$0</b>	<b>\$0</b>	

© Copyright 2008 Virginia Department of Transportation. All Rights Reserved.

VDOT Six-Year Improvement Program v1.0

## APPENDIX D: PUBLIC COMMENTS

The following public comment was received via 1-14-14 email:

Outstanding report.

Please consider noting that additional traffic signal timing type projects should be considered due to the following facts.

1. High B/C ratios
2. Quick implementation timeframes
3. Low costs

The following routes are suggested as possible additions to the list of this type of project.

1. Route 460 in Suffolk and west into the VDOT maintenance areas
2. Route 10 in Suffolk west into the VDOT maintenance areas
3. Route 17 in Suffolk and Isle of Wight between I-664 and the James River Bridge

Robert E. Lewis, P.E., FITE  
City Traffic Engineer  
City of Suffolk  
757-514-7603 (O)  
757-923-2491 (F)  
[relewis@suffolkva.us](mailto:relewis@suffolkva.us)  
[www.suffolk.va.us](http://www.suffolk.va.us)

"The information contained in this e-mail message and any files transmitted with it are intended only for the individual(s) listed above. If you have received this communication in error, please notify the sender and delete the material from any computer."

The City of Suffolk now has a new email domain name. It is [@suffolkva.us](mailto:@suffolkva.us). Please begin using this in the future. Thanks!  
(eg. [jdoe@city.suffolk.va.us](mailto:jdoe@city.suffolk.va.us) is now [jdoe@suffolkva.us](mailto:jdoe@suffolkva.us))

In response to this comment, the "Future Steps" sub-section was added under the "Conclusion" section.

The following public comment was received via 1-31-14 email:



**Gloucester County  
Administrator's Office**

Telephone 804-693-4042      P. O. Box 329, Gloucester, Virginia 23061      Fax 804-693-6004

January 31, 2014

HRTPO  
Attn: Robert N. Case, P.E., PhD.  
723 Woodlake Drive  
Chesapeake, Virginia 23320

RE: Prioritizing Highway Projects for Improvement of Hurricane Evacuation

Dear Mr. Case:

Thank you for the opportunity to review the referenced planning document. Gloucester recognizes the importance of the Route 17 corridor for the safe evacuation of citizens living both on the Virginia Peninsula and the Middle Peninsula. To this extent, we do believe that improvement to the signal coordination and timing specifically for evacuation is a worthy project. According to your analysis, this project is also one of the more cost effective projects with respect to improving traffic throughput.

With this said, I believe it may be important for you to realize that VDOT currently has two projects in the public input stage to improve signal timing along Route 17 in Gloucester (UPC 103763 and UPC 98806). If regional funding is available to implement the recommendations of the referenced plan, there may be opportunities to supplement the funding of these existing projects to expand their scope to include evacuation timing capabilities in a more cost effective manner compared to allowing them to move forward independently and be followed by a separate project to provide for evacuation timing.

Thank you again for the opportunity to provide comment.

Sincerely,

  
Garrey W. Curry, Jr., P.E.  
Assistant County Administrator  
for Community Development

pc: file  
Brenda Garton, County Administrator  
Anne Ducey-Ortiz, Director of Planning and Zoning  
Craig Moore, Emergency Management Coordinator

LAND OF THE LIFE WORTH LIVING

In response to this comment, a note was added to the "Identification of Highway Projects for Improving Hurricane Evacuation" section and an email reply was sent describing opportunities for funding (CMAQ and RSTP) available from the HRTPO.